



HARDWARE

DOCK

BOLT SIZE (INCHES)	OUTSIDE DIAMETER (INCHES)	HOLE DIAMETER (INCHES)	AMERICAN STANDARD GAUGE	APPROX. LB. PER M PCS.	APPROX. NO./PCS. PER LB
1/4	3/4	5/16	16 (1/16)	6.7	149.0
3/8	1	7/16	14 (5/64)	14.9	67.0
1/2	1-3/8	9/16	12 (7/64)	38.5	26.0
5/8	1-3/4	11/16	10 (9/64)	77.0	13.0
3/4	2	13/16	9 (5/32)	110.0	9.1
7/8	2-1/4	15/16	8 (11/64)	153.0	6.5
1	2-1/2	1-1/16	8 (11/64)	188.0	5.3
1-1/8	2-3/4	1-1/4	8 (11/64)	220.0	4.5
1-1/4	3	1-3/8	8 (11/64)	260.0	3.8
1-3/8	3-1/4	1-1/2	7 (3/16)	333.0	3.0
1-1/2	3-1/2	1-5/8	7 (3/16)	385.0	2.6
1-5/8	3-3/4	1-3/4	7 (3/16)	448.0	2.3
1-3/4	4	1-7/8	7 (3/16)	500.0	2.0
1-7/8	4-1/4	3	7 (3/16)	569.0	1.8
2	4-1/2	2-1/8	7 (3/16)	630.0	1.6
2-1/4	4-3/4	2-3/8	5 (7/32)	826.0	1.2
2-1/2	5	2-5/8	4 (15/64)	961.0	1.0
2-3/4	5-1/4	2-7/8	3 (1/4)	1100.0	0.9
3	5-1/2	3-1/8	2 (9/32)	1300.0	0.8

GALVANIZED FLAT WASHER (U.S.S.)



BOLT SIZE (INCHES)	OUTSIDE DIAMETER (INCHES)	HOLE DIAMETER (INCHES)	THICK	APPROX. WT. PER CPCS.	APPROX. NO. PER CWT
5/8	3	11/16	1/4	48.8	205.0
3/4	3	13/16	1/4	48.1	208.0
7/8	3	15/16	1/4	46.5	215.0
1	3-1/4	1-1/16	1/4	54.1	185.0
1-1/8	3-5/8	1-1/4	3/8	106.0	94.0
1-1/4	4	1-3/8	1/2	161.0	62.0

GALVANIZED DOCK WASHER



BOLT SIZE (INCHES)	OUTSIDE DIAMETER (INCHES)	HOLE DIAMETER (INCHES)	THICK	APPROX. WT. PER CPCS.	APPROX. NO. PER CWT
1/2	2-3/8	5/8	1/2	27.0	370.0
5/8	2-3/4	3/4	5/8	56.0	179.0
3/4	3	7/8	3/4	95.0	105.0
7/8	3-1/2	1	7/8	124.0	81.0
1	4	1-1/8	1	180.0	56.0
1-1/8	4-1/4	1-1/4	1-1/8	240.0	42.0
1-1/4	4-1/2	1-3/8	1-1/4	258.0	39.0
1-1/2	5-1/4	1-5/8	1-1/2	464.0	22.0

GALVANIZED O.G. WASHER

